

SAFETY DATA SHEET

Version 6.9 Revision Date 07/25/2023 Print Date 02/10/2024

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifiers

Product name	[:] Acetone
Product Number	: 179124
Brand	: SIGALD
Index-No.	: 606-001-00-8
CAS-No.	: 67-64-1

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses : Laboratory chemicals, Synthesis of substances

1.3 Details of the supplier of the safety data sheet

Company	: Sigma-Aldrich Inc. 3050 SPRUCE ST
	ST. LOUIS MO 63103 UNITED STATES
Telephone	: +1 314 771-5765

Fax : +1 800 325-5052

1.4 Emergency telephone

Emergency Phone #	: 8	300-424-9300 CHEMTREC (USA) +1-703-
	[527-3887 CHEMTREC (International) 24
	ŀ	Hours/day; 7 Days/week

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

GHS Classification in accordance with 29 CFR 1910 (OSHA HCS)

Flammable liquids (Category 2), H225 Eye irritation (Category 2A), H319 Specific target organ toxicity - single exposure (Category 3), Central nervous system, H336

For the full text of the H-Statements mentioned in this Section, see Section 16.

2.2 GHS Label elements, including precautionary statements

Pictogram



Signal Word SIGALD - 179124 Danger

Page 1 of 13



Hazard statement(s) H225 H319 H336	Highly flammable liquid and vapor. Causes serious eye irritation. May cause drowsiness or dizziness.
Precautionary statement(s)	
P210	Keep away from heat/ sparks/ open flames/ hot surfaces. No
P233	smoking. Keep container tightly closed.
P240	Ground/bond container and receiving equipment.
P241	Use explosion-proof electrical/ ventilating/ lighting/ equipment.
P242	Use only non-sparking tools.
P243	Take precautionary measures against static discharge.
P261	Avoid breathing mist or vapors.
P264	Wash skin thoroughly after handling.
P271	Use only outdoors or in a well-ventilated area.
P280	Wear protective gloves/ eye protection/ face protection.
P303 + P361 + P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.
P304 + P340 + P312	IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337 + P313	If eye irritation persists: Get medical advice/ attention.
P370 + P378	In case of fire: Use dry sand, dry chemical or alcohol-resistant
	foam to extinguish.
P403 + P233	Store in a well-ventilated place. Keep container tightly closed.
P403 + P235	Store in a well-ventilated place. Keep cool.
P405	Store locked up.
P501	Dispose of contents/ container to an approved waste disposal plant.

2.3 Hazards not otherwise classified (HNOC) or not covered by GHS

Repeated exposure may cause skin dryness or cracking.

SECTION 3: Composition/information on ingredients

3.1	Substances Formula Molecular weight CAS-No. EC-No. Index-No.	:	C ₃ H ₆ O 58.08 g/mol 67-64-1 200-662-2 606-001-00-8		
	Component			Classification	Concentration
	acetone				
				Flam. Liq. 2; Eye Irrit. 2A; STOT SE 3; H225, H319, H336 Concentration limits:	<= 100 %

SIGALD - 179124

Page 2 of 13



>= 20 %: STOT SE 3, H336;	
------------------------------	--

For the full text of the H-Statements mentioned in this Section, see Section 16.

SECTION 4: First aid measures

4.1 Description of first-aid measures

General advice

Show this material safety data sheet to the doctor in attendance.

If inhaled

After inhalation: fresh air. Call in physician.

In case of skin contact

In case of skin contact: Take off immediately all contaminated clothing. Rinse skin with water/ shower.

In case of eye contact

After eye contact: rinse out with plenty of water. Call in ophthalmologist. Remove contact lenses.

If swallowed

After swallowing: immediately make victim drink water (two glasses at most). Consult a physician.

4.2 Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

4.3 Indication of any immediate medical attention and special treatment needed No data available

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media Carbon dioxide (CO2) Foam Dry powder

Unsuitable extinguishing media

For this substance/mixture no limitations of extinguishing agents are given.

5.2 Special hazards arising from the substance or mixture

Carbon oxides Combustible. Pay attention to flashback. Vapors are heavier than air and may spread along floors. Development of hazardous combustion gases or vapours possible in the event of fire. Forms explosive mixtures with air at ambient temperatures.

5.3 Advice for firefighters

In the event of fire, wear self-contained breathing apparatus.

SIGALD - 179124

Page 3 of 13



5.4 Further information

Remove container from danger zone and cool with water. Prevent fire extinguishing water from contaminating surface water or the ground water system.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Advice for non-emergency personnel: Do not breathe vapors, aerosols. Avoid substance contact. Ensure adequate ventilation. Keep away from heat and sources of ignition. Evacuate the danger area, observe emergency procedures, consult an expert. For personal protection see section 8.

6.2 **Environmental precautions** Do not let product enter drains. Risk of explosion.

6.3 Methods and materials for containment and cleaning up Cover drains. Collect, bind, and pump off spills. Observe possible material restrictions (see sections 7 and 10). Take up with liquid-absorbent material (e.g. Chemizorb®). Dispose of properly. Clean up affected area.

Reference to other sections 6.4

For disposal see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling

Work under hood. Do not inhale substance/mixture. Avoid generation of vapours/aerosols.

Advice on protection against fire and explosion

Keep away from open flames, hot surfaces and sources of ignition. Take precautionary measures against static discharge.

Hygiene measures

Change contaminated clothing. Preventive skin protection recommended. Wash hands after working with substance.

For precautions see section 2.2.

7.2 Conditions for safe storage, including any incompatibilities

Storage conditions

Keep container tightly closed in a dry and well-ventilated place. Keep away from heat and sources of ignition.

Storage class

Storage class (TRGS 510): 3: Flammable liquids

7.3 Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

SIGALD - 179124

Page 4 of 13



SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Ingredients with workplace control parameters				
Component	CAS-No.	Value	Control	Basis
			parameters	
acetone	67-64-1	TWA	250 ppm	USA. ACGIH Threshold Limit
				Values (TLV)
	Remarks	Not classifi	able as a human	carcinogen
		STEL	500 ppm	USA. ACGIH Threshold Limit
				Values (TLV)
		Not classifi	able as a human	carcinogen
		TWA	250 ppm	USA. NIOSH Recommended
			590 mg/m3	Exposure Limits
		TWA	1,000 ppm	USA. Occupational Exposure
			2,400 mg/m3	Limits (OSHA) - Table Z-1
				Limits for Air Contaminants
		С	3,000 ppm	California permissible exposure
				limits for chemical
				contaminants (Title 8, Article
				107)
		PEL	500 ppm	California permissible exposure
			1,200 mg/m3	limits for chemical
				contaminants (Title 8, Article
				107)
		STEL	750 ppm	California permissible exposure
			1,780 mg/m3	limits for chemical
				contaminants (Title 8, Article
				107)

Ingredients with workplace control parameters

Biological occupational exposure limits

Component	CAS-No.	Parameters	Value	Biological specimen	Basis
acetone	67-64-1	Acetone	25 mg/l	Urine	ACGIH - Biological Exposure Indices (BEI)
	Remarks	End of shift (As soon as	possible after exp	osure ceases)

Derived No Effect Level (DNEL)

Application Area	Routes of	Health effect	Value	
	exposure			
Workers	Skin contact	Long-term systemic effects	186mg/kg BW/d	
Consumers	Ingestion	Long-term systemic effects	62mg/kg BW/d	
Consumers	Skin contact	Long-term systemic effects	62mg/kg BW/d	
Workers	Inhalation	Acute systemic effects	2420 mg/m3	
Workers	Inhalation	Long-term systemic effects	1210 mg/m3	
Consumers	Inhalation	Long-term systemic effects	200 mg/m3	

SIGALD - 179124

Page 5 of 13



Predicted No Effect Concentration (PNEC)		
Compartment	Value	
Soil	33.3 mg/kg	
Sea water	1.06 mg/l	
Fresh water	10.6 mg/l	
Sea sediment	3.04 mg/kg	
Fresh water sediment	30.4 mg/kg	
Onsite sewage treatment plant	100 mg/l	

8.2 Exposure controls

Appropriate engineering controls

Change contaminated clothing. Preventive skin protection recommended. Wash hands after working with substance.

Personal protective equipment

Eye/face protection

Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU). Safety glasses

Skin protection

This recommendation applies only to the product stated in the safety data sheet, supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de).

Full contact Material: butyl-rubber Minimum layer thickness: 0.7 mm Break through time: 480 min Material tested:Butoject® (KCL 898)

This recommendation applies only to the product stated in the safety data sheet, supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de). Splash contact

Material: Latex gloves Minimum layer thickness: 0.6 mm Break through time: 10 min Material tested:Lapren® (KCL 706 / Aldrich Z677558, Size M)

Body Protection

Flame retardant antistatic protective clothing.

Respiratory protection

Recommended Filter type: Filter type AX

The entrepeneur has to ensure that maintenance, cleaning and testing of respiratory protective devices are carried out according to the instructions of the producer. These measures have to be properly documented.

required when vapours/aerosols are generated.

Our recommendations on filtering respiratory protection are based on the following standards: DIN EN 143, DIN 14387 and other accompanying standards relating to the used respiratory protection system.

SIGALD - 179124

Page 6 of 13



Control of environmental exposure

Do not let product enter drains. Risk of explosion.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

a)	Appearance	Form: clear, liquid Color: colorless
b)	Odor	pungent, weakly aromatic
c)	Odor Threshold	0.1 ppm
d)	рН	5 - 6 at 395 g/l at 20 °C (68 °F)
e)	Melting point/freezing point	Melting point/range: -94 °C (-137 °F) - lit.
f)	Initial boiling point and boiling range	56 °C 133 °F at 1,013 hPa - lit.
g)	Flash point	-17.0 °C (1.4 °F) - closed cup
h)	Evaporation rate	No data available
i)	Flammability (solid, gas)	No data available
j)	Upper/lower flammability or explosive limits	Upper explosion limit: 13 %(V) Lower explosion limit: 2 %(V)
k)	Vapor pressure	245.3 hPa at 20.0 °C (68.0 °F)
I)	Vapor density	No data available
m)	Density	0.791 g/cm3 at 25 °C (77 °F) - lit.
	Relative density	No data available
n)	Water solubility	soluble, in all proportions
o)	Partition coefficient: n-octanol/water	No data available
p)	Autoignition temperature	465.0 °C (869.0 °F)
q)	Decomposition temperature	Distillable in an undecomposed state at normal pressure.
r)	Viscosity	No data available
s)	Explosive properties	No data available
t)	Oxidizing properties	none
Oth	ner safety informatio	on
	Conductivity	0.01 µS/cm at 20 °C (68 °F)
	Surface tension	23.2 mN/m at 20.0 °C (68.0 °F)

SIGALD - 179124

9.2

Page 7 of 13



SECTION 10: Stability and reactivity

10.1 Reactivity

Vapors may form explosive mixture with air.

10.2 Chemical stability

The product is chemically stable under standard ambient conditions (room temperature) .

10.3 Possibility of hazardous reactions

Risk of ignition or formation of inflammable gases or vapours with: chromosulfuric acid chromyl chloride ethanolamine Fluorine Strong oxidizing agents strong reducing agents Nitric acid chromium(VI) oxide Risk of explosion with: nonmetallic oxyhalides halogen-halogen compounds Chloroform nitrating acid nitrosyl compounds hydrogen peroxide halogen oxides organic nitro compounds peroxi compounds Exothermic reaction with: Bromine Alkali metals alkali hydroxides Halogenated hydrocarbon Sulfur dichloride phosphorous oxichloride

10.4 Conditions to avoid

Warming.

10.5 Incompatible materials

rubber, various plastics

10.6 Hazardous decomposition products In the event of fire: see section 5

SIGALD - 179124

Page 8 of 13



SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

LD50 Oral - Rat - female - 5,800 mg/kg Remarks: (ECHA) LC50 Inhalation - Rat - 4 h - 76 mg/l - vapor

Remarks: Unconsciousness Drowsiness Dizziness (External MSDS) LD50 Dermal - Rabbit - 20,000 mg/kg Remarks: (IUCLID)

Skin corrosion/irritation

Skin - Rabbit Result: Mild skin irritation - 24 h (Draize Test) Remarks: (RTECS)

Serious eye damage/eye irritation

Eyes - Rabbit Result: Eye irritation - 24 h (Draize Test) Remarks: (RTECS)

Respiratory or skin sensitization

Maximization Test - Guinea pig Result: Not a skin sensitizer. Remarks: (ECHA) Chronic exposure may cause dermatitis.

Germ cell mutagenicity

Test Type: Mutagenicity (mammal cell test): chromosome aberration. Test system: Chinese hamster ovary cells Metabolic activation: with and without metabolic activation Method: OECD Test Guideline 473 Result: negative Test Type: Ames test Test system: Salmonella typhimurium Metabolic activation: with and without metabolic activation Method: OECD Test Guideline 471 Result: negative Test Type: In vitro mammalian cell gene mutation test Test system: Mouse lymphoma test Metabolic activation: without metabolic activation Method: OECD Test Guideline 476 Result: negative

Carcinogenicity

IARC: No ingredient of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

SIGALD - 179124

Page 9 of 13



- NTP: No ingredient of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.
- OSHA: No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

Reproductive toxicity

No data available

Specific target organ toxicity - single exposure

Inhalation - May cause drowsiness or dizziness. - Narcotic effects

Specific target organ toxicity - repeated exposure

No data available

Aspiration hazard No data available

11.2 Additional Information

RTECS: AL3150000

To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated.

After absorption:

Headache Salivation Nausea Vomiting Dizziness narcosis Coma

Other dangerous properties can not be excluded.

Handle in accordance with good industrial hygiene and safety practice.

Kidney - Irregularities - Based on Human Evidence

Skin - Dermatitis - Based on Human Evidence

Kidney - Irregularities - Based on Human Evidence

Skin - Dermatitis - Based on Human Evidence

SECTION 12: Ecological information

12.1 Toxicity

Toxicity to fish

flow-through test LC50 - Pimephales promelas (fathead minnow) - 6,210 mg/l - 96 h (OECD Test Guideline 203)

SIGALD - 179124

Page 10 of 13



	Toxicity to daphnia and other aquatic invertebrates	static test LC50 - Daphnia pulex (Water flea) - 8,800 mg/l - 48 h Remarks: (ECHA)
	Toxicity to algae	static test NOEC - M.aeruginosa - 530 mg/l - 8 d (DIN 38412) Remarks: (maximum permissible toxic concentration) (IUCLID)
	Toxicity to bacteria	static test EC50 - activated sludge - 61.15 mg/l - 30 min (OECD Test Guideline 209)
	Toxicity to daphnia and other aquatic invertebrates(Chronic toxicity)	flow-through test NOEC - Daphnia magna (Water flea) - 2,212 mg/l - 28 d Remarks: (ECHA)
12.2	Persistence and deg	radability

2 Persistence and degradability Biodegradability aerobic - Exposure time 28 d Result: 91 % - Readily biodegradable. (OECD Test Guideline 301B)

Biochemical Oxygen	1,850 mg/g
Demand (BOD)	Remarks: (IUCLID)
Chemical Oxygen	2,070 mg/g
Demand (COD)	Remarks: (IUCLID)
Theoretical oxygen	2,200 mg/g
demand	Remarks: (Lit.)

12.3 Bioaccumulative potential Does not bioaccumulate.

12.4 Mobility in soil

No data available

- 12.5 Results of PBT and vPvB assessment PBT/vPvB assessment not available as chemical safety assessment not required/not conducted
- **12.6 Endocrine disrupting properties** No data available

12.7 Other adverse effects

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

Waste material must be disposed of in accordance with the national and local regulations. Leave chemicals in original containers. No mixing with other waste. Handle uncleaned containers like the product itself.

SIGALD - 179124

Page 11 of 13



SECTION 14: Transport information		
DOT (US) UN number: 1090 Class: 3 Proper shipping name: Acetone Reportable Quantity (RQ): 5000 lbs Poison Inhalation Hazard: No	Packing group: II	
IMDG UN number: 1090 Class: 3 Proper shipping name: ACETONE	Packing group: II	EMS-No: F-E, S-D
IATA UN number: 1090 Class: 3 Proper shipping name: Acetone	Packing group: II	

SECTION 15: Regulatory information

SARA 302 Components

This material does not contain any components with a section 302 EHS TPQ.

SARA 313 Components

This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

SARA 311/312 Hazards

Fire Hazard, Acute Health Hazard, Chronic Health Hazard

Massachusetts Right To Know Components

acetone	CAS-No. 67-64-1	Revision Date 1993-02-16
Pennsylvania Right To Know Components	CAS-No.	Revision Date
acetone	67-64-1	1993-02-16

SIGALD - 179124

Page 12 of 13



SECTION 16: Other information

Further information

The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. It does not represent any guarantee of the properties of the product. Sigma-Aldrich Corporation and its Affiliates shall not be held liable for any damage resulting from handling or from contact with the above product. See www.sigma-aldrich.com and/or the reverse side of invoice or packing slip for additional terms and conditions of sale.

Copyright 2020 Sigma-Aldrich Co. LLC. License granted to make unlimited paper copies

for internal use only. The branding on the header and/or footer of this document may temporarily not visually match the product purchased as we transition our branding. However, all of the information in the document regarding the product remains unchanged and matches the product ordered. For further information please contact misbranding@sial.com. Revision Date: 07/25/2023 Print Date: 02/10/2024 Version: 6.9

SIGALD - 179124

Page 13 of 13

